

CEMINTEL™ TOP COAT



4 EASY STEPS

THE CEMINTEL™ TEXTURE COATING SYSTEM IS COMPLETED IN 4 EASY STEPS:

STEP 1

Preparation Joints

Jointing Compounds and Tapes

STEP 2

Preparation Surface

Skim Coats

STEP 3

Texture Coat

Decorative and protective finish

STEP 4 ✓

Top Coat

Final coating



Cemintel™ Top Coat

ITEMS REQUIRED:

- (1) Cemintel™ Top Coat
- (2) Roller
- (3) Brush

PRODUCT DESCRIPTION:

Cemintel™ Top Coat is a water based pure acrylic coating formulated with 100% pure acrylic, mineral fillers and pigment. It is designed to overcoat Cemintel™ Texture Coatings providing a matt finish. Cemintel™ Top Coat will provide colour consistency, improved crack resistance, reduce long term dirt entrapment and increase mould and algae resistance.

The product can be applied using a roller, brush or airless spray device.

Your Top Coat is the final step in the process, your wall is now complete. Cemintel™ Top Coat is available in a wide range of colours tintable to your selection. See in store for more information.

APPLICATION:

- Before work ensure the preceding texture coat is dry, clean and free from imperfections. Only apply product in climatic conditions of between 10°C and 30°C.
- Mix product before use.
- Apply product using a 10-20mm nap roller. A 0.14mm film build is recommended to achieve good coverage.
- When using a brush to cut in certain areas ensure work is complete at once to avoid window framing effects.
- In most instances a single coat can be used. Where a second coat is required wait 3 hours before applying subsequent coats.
- Surface will need to be recoated following the above method every 7 years.

PRODUCT NOTES

DRYING TIME

Cemintel™ Top Coat should be touch dry in 1 hour, ready for recoat after 3 hours.

SHELF LIFE

The shelf life of the product is 12 months from the date of manufacture in the sealed bucket.

SAFETY

A material safety data sheet is available on request or www.csr.com.au.

COVERAGE

One bucket of Cemintel™ Top Coat will cover approximately 75m².

COLOUR

Product can be tinted to a range of colours excluding dark colours.

RECOAT

It is estimated that a recoat will be required in approximately 7 years from initial application.

For more information about the Cemintel™ Texture Coat System, visit your local distributor or call

1300 CEMINTEL (1300 236 468)
www.cemintel.com.au

CEMINTEL™ FIBRE CEMENT SYSTEMS,
CSR BUILDING PRODUCTS LIMITED, A.B.N. 55 008 631 356

F223