

PANEL DESCRIPTION / COMPOSITION

## Compressed Sheet

### APPLICATIONS

	Result
Applications	Flooring & Decking
Type of Building Structure	Residential Housing Buildings within the scope of AS4055, Commercial & Other (Limited loadings - refer to Design & Installation Guide)
Wet Areas	Yes

### PANEL - DIMENSIONAL & GEOMETRICAL CHARACTERISTICS

Dimensional/Geometrical Characteristic	Specification	Manufacturing Tolerance	Relevant Standard
Panel Dimensions	1200mmW x 2400L x 6mmD	Width +0 -3 mm	
	1200mmW x 2400mmL x 12mmD		
	1200mmW x 3000mmL x 12mmD	Length +0 -3 mm	
	900mmW x 1800mmL x 15mmD		
	900mmW x 2100mmL x 15mmD	Thickness +10% -0%	
	900mmW x 2400mmL x 15mmD		
	900mmW x 2700mmL x 15mmD		
	900mmW x 3000mmL x 15mmD		
	1200mmW x 1800mmL x 15mmD		
	1200mmW x 2100mmL x 15mmD		
	1200mmW x 2400mmL x 15mmD		
	1200mmW x 2700mmL x 15mmD		
	1200mmW x 3000mmL x 15mmD		
	900mmW x 2400mmL x 18mmD		
	900mmW x 3000mmL x 18mmD		
1200mmW x 1800mmL x 18mmD			
1200mmW x 2400mmL x 18mmD			
1200mmW x 3000mmL x 18mmD			
1200mmW x 2400mmL x 24mmD			
Profile	Square Edge		
Perpendicularity/squareness of edges	1mm/linear meter		
Weight (typical)	6mm = 11.9kg/m <sup>2</sup> , 12mm = 23.4kg/m <sup>2</sup> , 15mm = 29.25kg/m <sup>2</sup> , 18mm = 35.1kg/m <sup>2</sup>		

Layout Options	N/A
Joining	Butt Jointed, Sealant

#### PANEL - STRENGTH & MOISTURE RELATED PROPERTIES

Physical Property	Result	Relevant Standard
Modulus of Rupture (Wet)	>18MPa	AS2908.2
Modulus of Elasticity (Wet)	9-13GPa	AS2908.2
Density (Oven Dry)	1625 kg/m <sup>3</sup>	AS2908.2
Water Vapor Diffusion	Not Required	Not Required
Water Tightness (24hrs)	No water droplet	AS2908.2
Water Absorption (Saturated – 48hrs)	18 wt%	ASTM C 1186
Moisture Content (EMC)	7 Wt %	ASTM C 1186
Moisture Movement	0.039%	ASTM C 1186

#### PANEL - OTHER DURABILITY/WEATHER RESISTANCE INDICATORS

Test	Result	Relevant Standard
Heat Rain	PASSED (25 Cycles)	AS2908.2
Freeze Thaw	PASSED (50 Cycles)	AS2908.2
Warm Water Resistance	PASSED (56 days)	AS2908.2
Soak Dry	PASSED (25 Cycles)	AS2908.2

#### PANEL - FINISH CHARACTERISTICS

Characteristic	Result	Relevant Standard
Finish	Unprimed	
Coating Type		
Colour Bodied	No	
Paint Type		
UV Resistance	N/A	N/A
Formaldehyde Emission Rate	N/A	N/A
VOC Emission Rate	N/A	N/A

Spectral Reflectivity Values	Solar Reflectance %	Solar Absorption %	Basix Colour	Relevant Standard

## PANEL - FIRE RESISTANCE, THERMAL & ACOUSTIC PROPERTIES

Characteristic	Result	Relevant Standard
FIRE RESISTANCE		
Combustibility	Suitable for use in applications where non-combustible materials are specified by the Deemed to Satisfy Provisions of the 2016 BCA Vol 1 Amendment 1 Clause C1.9 (2015 BCA Vol Clause C1.12)	
Fire Hazard Properties	Group 1 Av Specific Extinction Area <250	AS/NZ 3837
Classification	1	AS/NZ 3837
Surface Burning Characteristics	Ignitability =0, Flame Propagation =0, Heat Release =0, Smoke Release=1	AS1530.3
THERMAL CONDUCTIVITY		
Thermal Conductivity ( $\lambda$ -Factor)	$\approx 0.4108 \text{ W/m.K.}$	
Thermal Expansion Co-efficient	0.005-0.01mm/mK	N/A
ACOUSTIC VALUE		
Sound reduction (depends on construction)	N/A	N/A

## SYSTEM SOLUTIONS

Characteristic	Result	Relevant Standard
Within Scope of AS4055?	Yes	
Wind Loading - Residential housing buildings within the scope of AS4055	N/A	
Weatherproofing	N/A	N/A
Cyclonic Conditions	N/A	N/A
Fire Resistance Limits (FRLs)	Up to 120/120/120 & -/180/180	Refer to Gyprock® The Red Book™
Bushfire Construction	BAL 40 (Construction for Bushfire Attack Level 40 for an external wall)	AS 3959-8

Acoustic	Acoustic solutions of up to RW/RW+CTR 56/47 are detailed	Refer to Gyprock® The Red Book™
Thermal	Thermal solutions of up to RT(sum)/RT(win) 3.5/3.8 are detailed	Refer to Gyprock® The Red Book™

## FIXING

### Characteristic

Maximum Span (Stud Spacing) Up to 450mm (15mm). Up to 600mm (18mm).

### DIRECT FIX

Nail to Timber Frame No

Screw to Timber Frame Yes

Screw to Steel Frame Yes

### INDIRECT FIX

Timber Frame No

Steel Frame No

Masonry Frame No

### EXPOSED FASTENERS

Screw No

Rivet No

Nail No

### CONCEALED FASTENERS

Clip No

Countersunk Screw/Nail Yes

Adhesive, Split Batten, etc. Yes

Hidden by Overlapping Panel No

Flush Jointed (Taped) No

## WARRANTY

25 YEARS

February 24, 2019